



PROFESSIONAL NETWORKING PRODUCT SHEET

Fast, Simple, unlocked 4G MiFi Router

Model No: M80

The TOPLINK M80 LTE 4G HSPA Mobile Router enables you to access worldwide mobile oadband networks. Once connected, you can enjoy seamless media streaming and data transmission on the go. Share your Internet connection through a secure wireless network by simply inserting your 4G LTE SIM card. The TOPLINK M80 can be configured to work as a 4G modem or a WiFi router. Instead of limiting your SIM card's Internet connection to a single device through a USB dongle, the TOPLINK M80 enables you to create a WiFi hotspot to share the same. Available in a black finish, the TOPLINK M80 LTE 4G Mobile Router provides you with an instant mobile access to the Internet for all your devices.







Size



Connect Protect

•

10 Devices



TOPLINK M80 موجه السلكية وحدة الوصول الى شبكة الجيل الثالث 4g أسود

TOPLINK M80 معيار واي فاي: Wi-Fi 4 (802.11n), معدل نقل بيانات TOPLINK M80 (الأقصى): TOPLINK M80 نوع الشبكة المحلية الاسلكية (Wi-Fi: 802.11b,802.11g,Wi-Fi 4 (802.11n), معايير G: Edge, GPRS معايير GG: Edge, GPRS دعم خوارزميات الحماية: اس إم, معايير AES,TKIP,WPA,WPA2-PSK نوع المنتج: موجه محمول router, لون المنتج: أسود, مؤشرات الصمام الثنائي المشع (LED: نشاط, الوضعية. نوع الانتينا الهوائي: داخلي

Product Specification

- 1. Supporting Global Network LTE-FDD / UMTS.
- 2. LTE CAT4 Up to 150Mbps.
- 3. Support up to 10 users to access internet.
- 4. 2400mAh battery, up to 5-7 hours working time.
- 5. LED indicators, working status displayed clearly.

Key Feature:

Charger:

4G LTE B1/B3/B38 With 150Mbps download

3G UMTS B1(2100MHz)
Chipest MDM9200

SIM Card Micro SIM Card (3FF)
Display 4 x LED Indicators

Wi-Fi Wi-Fi 802.11 b/g/n. Up to 10 users

Battery 2400 mAh Li-ion Battery
External Memory Support Max 32GB TF Card
Size & weight 120 x 90 x 50mm, 100G

Network Lock
Port:

1x Micro USB
1x Standard USIM

5V DC±10%; 1A

OS support: Windows; Mac; Linux; Android;

Operating Temp 0 to 40 °C (32 to 104 °F)

Storage Temp -20 to 70 °C (-4 to 158 °F)

Operating Humi 10% to 90% (non-condensing)

